



BIMSTEC
ENERGY CENTRE

Bay of Bengal Initiative for Multi-Sectoral
Technical and Economic Cooperation



Hot Line Maintenance in Transmission Lines



पावरग्रिड
POWERGRID

By

Sh. Murali M, Sr.DGM

Sh.V. Venkateswar Rao, DGM

Objective

To Know about,

HLM Principle

Type of HLM Operations

Safety aspects

Insulated Aerial Work Platform(IAWP) / Hot Line
Bucket Truck

HLM (Hot Line maintenance)?

A preventive maintenance Technique adopted in Transmission Lines and Substations for replacing defective insulators, Jumpers, Vibration Dampers, rectifying shutdown nature defects, etc. without availing shutdown on the Line / Bay, To achieve maximum availability.

Principle

- In 1937, Michel Faraday proved that there can be “**NO flow of ELECTRICITY** between two points at the same potential”.
- This principle is made use of in working on **hot line** by the **Bare Hand Techniques**
- 1959: The new light weight **EPOXY GLASS** for **Hot Line Tools** were introduced

LIVE LINE MAINTENANCE:

➤ HOT STICK METHOD :

In this method the lineman will be at ground potential working with Hot Sticks (tools) keeping safe clearance from the line.


➤ BARE HAND METHOD :

Here the lineman will be working at line potential keeping safe clearance from ground. For this insulated suits made of 25% Microscopic Stainless Steel and 75% NOMEX will be provided.


➤ COMBINATION METHOD :

This method is a combination of above two methods

Hot Stick Technique




Hot Stick also known as a "Distance" Technique



Up to 220 kV

Hot Stick Technique- Safety Distance



Hot Stick Technique- Approaching Methods

Ground



Platform



Ladder



Aerial Platform




Pole




Tower



Bare Hand Technique




Bare Hand also known as a "Potential" Technique



Above 132 kV

Bare Hand Technique- Safety Distance



Bare Hand Technique- Approaching Methods

Ladder



Aerial Platform



Chair



Scaffolding



Helicopter



Swivel Boom



Mixed of the above two methods



- Combination of HSM and BHM are used in all the voltages by observing the field conditions like clearances, atmosphere, line crossings etc.

Important Tools

- **Epoxy Sticks**
- **Conductive Suit**
- **Leakage Current Monitor**
- **Hotstick Tester**

A decorative graphic on the left side of the slide, consisting of overlapping yellow, red, and blue squares with a black crosshair.

EPOXY GLASS STICKS

- It is made up of thousands of epoxy glass resin impregnated glass fibre laid length wise and wound wise on a unicellular glass foam core, which is made up of millions of unconnected cells filled with inert gas. (The inert gas inhabits moisture absorption and condensation)

Advantages of Epoxy Glass Stick.

1. Higher Insulation value. (100 kV / foot)
2. Mechanically stronger.
3. No moisture absorption.
4. Orange colour for easy identification.
5. No effect on the sticks due to sudden changes in Temp. or atmospheric condition.
6. No effect of chemically polluted atmosphere.
7. Superior than wooden sticks.
8. Handling easy because of light in weight.
9. Maintenance is easy.

Conductive Suits

- Top, Bottom, Socks, Gloves, Grounding straps & Leg Straps
- Made Up of 25% Microscopic Steel Fiber & 75% NOMEX Aramid Flame Resistant Fiber, with repel finish
- High Conductivity of 144 Ohms/Sq.inch

Protective Conductive Wear- Bare Hand Work



Conductive Suit



Conductive Gloves and Socks



Conductive Boots



Leakage Current- Live Line Work on Transmission Line



This is the current that circulates through an insulating material placed between an energized point and an insulated point.

It flows through insulator strings, insulating poles, ladders, ropes etc. which are contact with potential.

Leakage Current Monitor

- This kit is used for measuring leakage current passing through ladder used during hot line maintenance work.
- The Kit includes one coaxial cable and battery and hose clamps to connect to ladder rail
- The monitor sounds an alarm if leakage current reaches a preset level
- The actual current level is continuously displayed on the digital screen
- If the leakage current is less than $100\mu\text{A}$, then it is safe to work



Hot Stick Tester

- Hot stick tester provides a means for testing epoxy hot sticks up to 3 inches
- This tester will detects surface contamination, internal moisture and internal conductive materials.
- Insulation level of epoxy glass hot stick is generally 100 KV per ft.



The background of the slide is a photograph of two workers in white protective suits and hoods performing maintenance on a high-voltage power line. One worker is positioned on a red metal ladder attached to the line, while the other is further back. The scene is set against a backdrop of a dense green forest under an overcast sky.

Safety during Hot line Maintenance Works

HOT LINE MAINTENANCE - SAFETY RULES



- Only Authorized/Trained persons should do hot line maintenance.
- Make sure that weather is clear and there is no chance of rain.
- Equip with HLM safety PPEs.
- Keep high degree of coordination among all while working.

HOT LINE MAINTENANCE - SAFETY RULES



- Maintain the safe working distances.
- Do not climb towards the jumper: if clearance is less push the jumper.
- Make proper plan to carry out the work in advance
- In-charge of work should not do work with his own hands. He should take such a position on the ground from where he can see all the working persons and should instruct them properly.

HOT LINE MAINTENANCE

DO'S



1. While taking PTW for HLM work in lines, ensure that the auto Re-closure is kept on Non-Auto mode at both ends
2. Thoroughly understand the work to be done and the method of doing it. In case of doubt, discuss and get clarified from the HLM Engineer In-charge
3. Take up Hot line work only when the weather is clear and there is no chance of rain.

HOT LINE MAINTENANCE

DO'S



4. Remove the wrist watch, rings, bracelets and any other metal ornaments before climbing the tower
5. Inspect all the tools carefully before and after every operation
6. Clean the hot sticks with moisture eater before sending it to the tower
7. Be extremely careful while transporting/ handling/ using the tools so as not to damage them or foul/ hit the tower

HOT LINE MAINTENANCE



DO'S

8. Check the insulation strength of the sticks with the help of the Hot stick Tester, If required.
9. Do the Leakage Current Test on the ladders / Platforms before deployment/sending HOTMAN to the charged conductor.
10. Take proper position in the tower and ensure that you are safe to work with both hands.

HOT LINE MAINTENANCE

DO'S



11. The HOT MAN should use the static belt, Hot gloves and protective goggles without fail.
12. The HOT MAN should ensure that the conductive suit is electrically bonded to the safety shoes through the band provided in the shoes.
13. Lubricate the rotation parts with silicon lubricants (Graphite Powder) only.

HOT LINE MAINTENANCE



DON'Ts

1. Do not climb towards LIVE JUMPER
2. Do not use any tool or equipment that is not designed, tested and intended for live line work.
3. Do not use any tool or equipment that is defective or damaged.
4. Do not keep any tool directly on the ground, as it is possible that they may absorb moisture which would reduce the dielectric strength.

HOT LINE MAINTENANCE



DON'Ts

5. Do not over load/ over stress the platform, supports, hot sticks, etc., by attempting to lift or support weights in excess of the manufacturer's rating.
6. Do not engage in any other task during live line maintenance in progress.
7. Do not be in a hurry up or loose patience

HOT LINE MAINTENANCE

DON'Ts




8. Do not engage in to conversation with fellow workers other than absolutely concerning the work.
9. Do not throw tools or materials to or from linemen on the structure.
10. Do not carry any tools in the Safety Belt. Tool bags should be used for this purpose.
11. Do not change position on the structure without first making certain that the new position will place you with all clearances.

HOT LINE MAINTENANCE DON'Ts



12. Do not change position without informing the fellow workmen as to what you intend to do.
13. Do not use grease or oil for lubricant as they do not provide the required insulation.



Any Doubts ?

As we proceed
further



Working on Live Potential, one must aware the Effect of Voltage /
Current on a human body

EFFECT OF CURRENT FLOW IN BODY


0 - 1 mA	Cannot feel anything
1 - 8 mA	Can feel but no pain
8 - 12 mA	Painful but can let it go
12 - 20 mA	Freeze, cannot let go
20 - 50 mA	Breathing stops
50 - 200 mA	Heart stops
200 and above	Sever Burns

In order to resist the passage of shock currents through the human body, the safe clearances has to be maintained between Ground and Live potentials.


SAFE WORKING DISTANCE FOR HLM


Phase to Phase kV	FEET	METRE
11	2'0	0.61
33	2'4"	0.71
66	3'0"	0.91
110	3'4"	1.02
132	3'6"	1.07
220	5'0"	1.52
400	7'0"	2.13

Hot Stick Method- Safety Distance Zone



Bare Hand Method- Safety Distance Zone






Hotman's Envelope

'E': Radius about 4 feet

'D' $\geq$ Safety Distance

Moving Ladder- Hoisted or Swung into the Working Position

Bare Hand Method- Safety Distance Zone



2E: Hotman's Envelope= 8 feet


'D' $\geq$ Safety Distance

$D_1 + D_2 \geq$ Safety Distance

Moving Ladder- Hoisted or Swung into the Working Position


Bare Hand Method- Safety Distance Zone

D1 + D2 ≥ Safety Distance



**Bare
Hand Chair**

Bare Hand Method- Safety Distance Zone



Effective Utilisation of HLM

Type of Operations

- Insulator replacement works (I, V, Tension, Pilot) in Transmission Lines
- Vibration Damper, Spacer, Spacer Damper and conductor Repair (Providing Armour Rods) in Transmission Lines
- Fixing Jumper Bolts, CC Rings & Rigid Spacer















Special Type of HLM Work: Replacement of single suspension insulator strings with double suspension insulator strings





Innovative Method: By HLM method provided Bypass arrangement for Mid Span Compression Joints (MSCJ) of Sub-Conductors in 765kV Transmission Lines, by which conductor snapping / falling will be avoided due to MSCJ failure and line tripping/outage will be avoided.

Failure of Mid Span Compression Joint (MSCJ) in Transmission Line



- MSCJ failed in one of the 765kV line due to improper compression causing snapping of conductor.
- The said line is **heavily loaded** and **getting outage is difficult** due to system constraints.



Innovative Hotline Maintenance work carried in 765kV Transmission Line

- The suspected MSCJ by passing activity was carried out in 765kV Transmission Line by **Hotline Maintenance Method**




Innovative Hotline Maintenance work carried in 765kV Transmission Line



Degree of System improvement: Averting long outage of Transmission element and maintaining the system availability and reliability of GRID in case of contingency.

Innovative Method: Installation of Dynamic Line Loading (DLL) Sensors carried out in 400kV Transmission Line of POWERGRID by Hotline Bare Hand Technique



Uniqueness / Innovation: Installation of Dynamic Line Loading (DLL) Sensor in 400kV Transmission Line

- First Time in POWERGRID, has successfully installed DLL Sensors in 400kV Transmission Line by Hotline Bare Hand Technique.
- Dynamic Line Loading (DLL) is a key grid enhancing technology, crucial for the energy transition, designed to ensure optimal infrastructure usage by using real-time data to determine the capacity of the line.



Uniqueness / Innovation: Installation of Dynamic Line Loading (DLL) Sensor in 400kV Transmission Line



- This technology helps prevent overloads, optimizes transmission usage, and supports the integration of renewable energy sources.



Uniqueness / Innovation: Installation of Dynamic Line Loading (DLL) Sensor in 400kV Transmission Line

- By adapting to changing conditions, DLL **reduces the risk of power cuts**, **mitigates bottlenecks in the grid**, and ensures a **stable power supply**.
- These GPS enabled Sensors are capable of measuring Phase Current, Conductor Temperature, Inclination Angle (Sag), Wind Speed & Humidity and send **data every 15 seconds** via SIM (Airtel) installed in each Sensor.
- The received data can be **monitored online** by cloud based web-dashboard software.



Any Doubts ?
As we proceed
further



Possible HLM works in SS area

- Replacement of SS disc insulator strings
- Replacement of bus droppers
- Cleaning and lubrication of live EHT isolators
- Removal of bird nest sheltered under the protection covers of EHT isolators
- Tightening of red-hot / loosen bolts and nuts.
- Rectification of damaged conductors, etc.


In Substation



In Substation



Scaffolding Operation in Substation



Hotline Maintenance Works using Insulating Modular Scaffolding Equipment **in 220kV and 400kV charged level at 400/220kV Substation Switch yard**



Replacement of damaged rigid spacer in Jumper in 400kV Switch yard was carried out using Insulated Modular Scaffolding Equipment

Hot Line Maintenance using Insulated Modular Scaffolding System



Rectification of T-Clamp of Jumper in ICT Bay of 400kV Switch yard was carried out using Insulated Modular Scaffolding Equipment

Scaffolding Operation



Rectification of damaged conductor of 220kV Jack bus connected to 220kV side of ICT in 220kV SwitchYard was carried out using Insulated Modular Scaffolding Equipment.

HLM Works using Hot line Ladder and Scaffolding System in 400kV Switchyard



Isolator Bypass Arrangement made in Hotline in 400kV Switch Yard





Rectification of jammed terminal stud of isolator was carried out in 400kV switchyard

The background image shows a worker in a white protective suit and helmet, positioned on a red insulated aerial work platform (IAWP) or bucket truck. The worker is working on a high-voltage power line. The background is a dense tropical forest with many palm trees under a clear sky.

**EXPERIENCE / KNOWLEDGE SHARING WITH
INSULATED AERIAL WORK PLATFORM (IAWP) /
TELESCOPIC INSULATED BUCKET TRUCK**


Insulated Aerial Work Platform (IAWP) / Telescopic Insulated Bucket Truck




Details of 765kV AC Telescopic Insulated Bucket Truck


Key Features of the Bucket truck

Insulated and Non-insulated Parts




Aerial Platform- Capacities & Dimensions





Platform Contacts with Potential



No Insulation

Insulated Aerial Work Platform (IAWP) :


Measuring of Leakage Current



Insulated Aerial Work Platform (IAWP) :Sending Hotmen



Insulated Aerial Work Platform (IAWP) : HOTMEN AT LIVE POTENTIAL



Replacement of defective insulator string with new insulator String in middle phases in 400kV S/C Transmission line using Hot Line Telescopic insulated bucket Truck



HLM Operations with Telescopic Insulated Bucket Truck

Jumper Spacer Rectification work in Transmission Line



HLM Operations with Telescopic Insulated Bucket Truck

Replacement of defective insulator string with new string






HLM Operations with Telescopic Insulated Bucket Truck : Carried out in 765kV Switchyard : Spacer dropper rectification work



HLM Operations with Telescopic Insulated Bucket Truck

:Rectification of opened spacers of jack bus jumpers connected to ICT Bay in 400kV Charged Switch yard



Photos








Hot-man Travel



Bucket Operation @765kv Switch Yard



400kv Isolator Opening in charged condition by HLM Method



Provided Bypass arrangement for Mid Span Compression Joints (MSCJ) in 765kV Transmission Line by HLM Method



Think Safely

Plan Safely

Work Safely

**Thank
You**

22 05 2023



Any Questions?



Thank You!

ধন্যবাদ
সুগমকে
ধন্যবাদ
ကျေးဇူးတင်ပါတယ်
ধন্যবাদ

මමට ස්තූතියි
ආචාර්ය

**For your valuable attention and commitment
to a sustainable energy future across BIMSTEC nations!**





BIMSTEC ENERGY CENTRE

**Bay of Bengal Initiative for Multi-Sectoral
Technical and Economic Cooperation**