

From Cell Chemistry to Real-World Performance



Presented By:
Dr. Puneeth S B,
CTO, HubEnergys

REAL-WORLD PERFORMANCE DRIVERS

"Behind those numbers is an electrochemical system whose true delivery is governed by key underlying factors:"



1. Chemistry

Fundamental electrochemical characteristics



2. Construction

Cell, module, and pack design architecture



3. Operating Conditions

Thermal environment & duty cycle stresses



4. Controls

BMS & software dispatch strategies

Why Energy Storage Matters



Renewable Penetration

Managing high-share intermittent generation across modern power grids.



Solar & Wind Variability

Smoothing non-dispatchable supply fluctuations in real time.



Peak Demand & Shifting

Mitigating peak loads and balancing diurnal demand profiles.



Grid Flexibility

Providing fast frequency response, inertia, and ancillary services.



Electrification & Charging

Supporting high-power EV charging clusters and industrial electrification.



Reliability & Resilience

Ensuring grid stability, black-start capabilities, and backup power.

What is a BESS?

A battery is only one part of the complete system.



1. Electrochemical Storage

Battery cells & modules that chemically store energy



2. Power Conversion

Inverters (PCS) converting DC to AC power bidirectionally



3. Controls

BMS & EMS software managing operations and state-of-charge



4. Thermal Management

HVAC & liquid cooling systems regulating optimal temperatures



5. Protection

Fire suppression, safety containment, and electrical safeguards



6. Grid Interface

Transformers & switchgear for high-voltage grid interconnection

Power, Energy, and Duration

LONG DURATION CONFIGURATION

25 MW / 100 MWh



~4 hours at rated output under stated conditions

SHORT DURATION CONFIGURATION

100 MW / 100 MWh



~1 hour at rated output under stated conditions



KEY TAKEAWAY

Same power rating does not mean same application or value.



“Before discussing applications, we need to understand what determines the behaviour of the battery itself.”

What Determines Cell Capacity?



Active Material

Volume and mass of electrochemically active materials.



Electrode Design

Coating thickness, porosity, and loading density.



Cell Size

Physical dimensions and internal volume available.



Material Utilization

Efficiency of active material during charge/discharge.



Manufacturing Quality

Precision in assembly, purity, and coating consistency.



CRITICAL DISTINCTION

A larger cell does not automatically mean a better cell.

The cell design must be precisely matched to the required energy, power, thermal, and lifetime performance demands of the target application.

Types of Battery Cells & Internal Mechanics

CELL FORM FACTORS



Cylindrical cell

- Cost efficient
- Easy to manufacture
- No casing require
- Strong mechanical resistance



Prismatic cell


- deliver more power and store more energy
- better heat management
- Preferred cell chemistry (lithium iron phosphate)



Pouch cell

- to deliver more power than other cell types
- soft plastic casing
- lowest mechanical resistance

LITHIUM-ION CELL STRUCTURE




Key Components:

- Anode & Cathode
- Electrolyte
- Separator
- Current Collectors

ELECTROCHEMICAL CHARGE & DISCHARGE CYCLE

Charging Process

Lithium ions (Li^+) move from the positive electrode to the negative electrode.



Discharging Process

Lithium ions (Li^+) move from the negative electrode to the positive electrode.

Comparison of Cell Form Factors



Cylindrical

MECHANICAL CONSTRUCTION – Rigid metallic

PACKAGING EFFICIENCY – Lower volumetric efficiency

THERMAL MANAGEMENT – Good heat dissipation

MANUFACTURING – Highly automated, mature high-speed production with high yield and lower cost.

INTEGRATION (PACKS) – Requires numerous electrical connections (wire bonding); strong structural frame.



Prismatic

MECHANICAL CONSTRUCTION – Rigid rectangular metallic shell

PACKAGING EFFICIENCY – High packaging efficiency;

THERMAL MANAGEMENT – Large flat surfaces facilitate efficient side cooling via integrated cold plates.

MANUFACTURING – Complex process requiring precise laser welding for heavy terminals and casing.

INTEGRATION (PACKS) – Fewer electrical connections needed; robust build simplifies module assembly.



Pouch

MECHANICAL CONSTRUCTION –

Flexible aluminum-laminated pouch

PACKAGING EFFICIENCY – Highest cell-level energy density,

THERMAL MANAGEMENT – Excellent surface heat removal

MANUFACTURING – Requires cleanroom conditions

INTEGRATION (PACKS) – Needs external mechanical support frames and compression hardware to prevent expansion.

Energy Density vs Power Capability



STORAGE CAPACITY

Energy Density

How much energy can be stored relative to the size or mass of the cell.

Determines total operating range and duration between charges.



DELIVERY SPEED

Power Capability

How quickly energy can be delivered or accepted by the cell.

Determines peak acceleration, fast-charging rates, and discharge rates.



KEY APPLICATION TRADE-OFF

High energy density does not equal high power optimization.

A cell designed strictly for high energy density is not necessarily optimized for repeated, high-power charging and discharging cycles without thermal stress or accelerated degradation.

The Cell is the Foundation of System Performance



Cell Chemistry

Fundamental materials (LFP, NMC) dictating intrinsic voltage and thermal safety.



Cell Design

Form factor, electrode thickness, tab structures, and internal mechanical geometry.



Manufacturing Quality

Precision coating consistency, purity, and strict tolerance control in production.



Operating Conditions

Thermal exposure, charge/discharge rates, C-rates, and depth of discharge.

▽ COMBINES TO DETERMINE CELL PERFORMANCE ▽




NEXT-LEVEL SYSTEM INTEGRATION

A cell does not operate alone.

A Battery Energy Storage System (BESS) is an engineered system built around thousands of interconnected cells, requiring advanced thermal management, structural integration, and controls.

The Battery Hierarchy: From Cell to Grid



SYSTEM INTEGRATION OVERVIEW

Scaling from Microscopic Chemistry to Megawatt-Scale Power

Each tier adds mechanical structure, thermal control, and intelligence. Safe grid-scale storage requires seamless integration from single cell electrochemistry all the way through power conversion to high-voltage AC delivery.

Why Cells Are Connected in Series and Parallel

SERIES CONNECTION Increases Total Voltage



- **Voltage Stacking:** Connecting cells end-to-end (positive to negative) adds their voltages together.
- **High-Power Efficiency:** Higher voltage enables greater power delivery to drive heavy system loads effectively.
- **Constant Capacity:** The total overall amp-hour (Ah) capacity remains identical to a single cell.

PARALLEL CONNECTION Increases Capacity & Current



- **Capacity Addition:** Connecting like terminals (positive-to-positive) sums the storage capacity (Ah).
- **Current Sharing:** Distributes total current load across multiple cells, extending overall runtime.
- **Constant Voltage:** The output voltage remains equal to the potential of a single individual cell.



PACK DESIGN STRATEGY

Balancing Electrical Behaviour & Redundancy

Combining series and parallel arrangements (sXp configuration) shapes the system's exact electrical characteristics. Parallel strings provide built-in fault tolerance and redundancy, preventing a single weak cell from failing the entire pack.

BESS SYSTEM ARCHITECTURE

How the Cell Becomes a Reliable BESS

BMS

Monitors cell voltage, temperature, current, SOC, and SOH. Performs active balancing and safety protection.

Thermal Mgmt

Maintains temperature uniformity across cells. Controls heat during high-rate charging and discharging.

PCS

Converts power between DC and AC. Controls charge and discharge rates to meet grid demands.

EMS

Determines dispatch schedules. Optimizes when and how the system charges or discharges based on grid loads.

Safety & Protection

Provides electrical isolation, fault detection, fire suppression, and emergency shutdown protocols.



KEY INTEGRATION TAKEAWAY

Cell Chemistry Defines Potential; Systems Guarantee Performance

While chemistry determines maximum potential performance, actual operational reliability, safety, and lifespan depend entirely on cell quality, controlled operating conditions, robust thermal management, and intelligent control systems.

Battery Technology Landscape

ESTABLISHED

Lithium-ion



LFP, NMC, and other proven chemistries dominating utility and EV applications today.

RAPIDLY EMERGING

Sodium-ion



Alternative intercalation chemistry utilizing abundant sodium for lower-cost stationary storage.

LONG DURATION

Flow Batteries



Liquid electrolyte-based storage, including vanadium redox systems for multi-hour energy supply. (Vanadium Redox Flow Battery)

NEXT-GENERATION

Emerging Tech



Solid-state, zinc-based, metal-air, and novel chemistries currently progressing through R&D.



COMMERCIAL MATURITY DIFFERENCES

Not all battery technologies sit at the same stage of market readiness.

While Lithium-ion dominates present deployments, Sodium-ion and Flow systems address specific cost and duration niches, whereas Emerging technologies represent long-term innovation pipelines.

LFP: Lithium Iron Phosphate

CHEMISTRY & STRUCTURE

Cathode Material



Stable olivine crystal structure using abundant iron and phosphate, offering non-toxic and cost-effective cathode material.

STABILITY & RISKS

Thermal & Safety



Exceptional thermal runaway resistance, high chemical stability, and robust safety under abuse or high temperatures.

LONGEVITY

Cycle Life



Long operational lifespan delivering 3,000 to 6,000+ deep charge-discharge cycles with low degradation.

TRADE-OFFS

Energy Density



Lower volumetric/gravimetric energy density compared to NMC, fully acceptable in stationary applications.

APPLICATIONS

Stationary Power



Dominates grid-scale BESS due to lower total cost of ownership, high reliability, and superior safety profile.



INDUSTRY PERSPECTIVE

The Premier Choice for Utility & Stationary Storage

LFP is widely relevant because it offers a strong balance of safety, cost, cycle life, and commercial maturity. Its lower energy density is a minor compromise in stationary storage where footprint is secondary to reliability and life-cycle economics.

LFP: Lithium Iron Phosphate

CHEMISTRY & STRUCTURE

Cathode Material



Stable olivine crystal structure using abundant iron and phosphate, offering non-toxic and cost-effective cathode material.

STABILITY & RISKS

Thermal & Safety



Exceptional thermal runaway resistance, high chemical stability, and robust safety under abuse or high temperatures.

LONGEVITY

Cycle Life



Long operational lifespan delivering 4,000 to 11,000+ deep charge-discharge cycles with low degradation.

TRADE-OFFS

Energy Density



Lower volumetric/gravimetric energy density compared to NMC, fully acceptable in stationary applications.

APPLICATIONS

Stationary Power



Dominates grid-scale BESS due to lower total cost of ownership, high reliability, and superior safety profile.



560Ah
Super-large capacity
1.792kWh
Energy
12000+
Life cycles

NMC: Nickel Manganese Cobalt

CHEMISTRY & STRUCTURE Cathode Material



Layered oxide structure blending nickel, manganese, and cobalt to maximize energy storage capacity.

PERFORMANCE Energy Density



Higher volumetric and gravimetric energy density potential, ideal for compact footprint demands.

ECONOMICS Material & Cost



Higher raw material cost and supply chain exposure due to reliance on cobalt and nickel pricing.

STABILITY & RISKS Thermal & Safety



Requires stricter thermal management and robust cooling controls due to lower thermal runaway threshold.

APPLICATIONS Space-Constrained



Critical for premium EVs and space-restricted storage where maximum energy per volume is essential.



CHEMISTRY COMPARISON & TRADE-OFFS

LFP and NMC represent strategic trade-offs, not pure superiority.

LFP and NMC are not simply “better” or “worse.” They represent different trade-offs within the lithium-ion family, balancing energy density, cost, safety, and lifespan based on application needs.

Sodium-ion: Emerging Storage Alternative

PRINCIPLE Intercalation



Operates via sodium-ion movement between electrodes, mirroring lithium-ion mechanics with larger ions.

SUPPLY CHAIN Abundant Materials



Uses widely available, low-cost sodium and iron, eliminating reliance on lithium and cobalt supply chains.

PERFORMANCE Energy Density



Lower energy density compared to leading lithium-ion cells, trading compactness for cost advantages.

APPLICATIONS Stationary Storage



Ideal for cost-sensitive stationary storage and grid applications where footprint constraints are minimal.

ECOSYSTEM Rapid Scale-Up



Leverages existing lithium-ion manufacturing processes, accelerating commercial scale and maturity.

STRATEGIC ROLE & POSITIONING



Sodium-ion broadens the storage landscape rather than replacing lithium-ion.

Sodium-ion introduces a complementary, highly scalable alternative that mitigates raw material risks and reduces costs for stationary applications, sitting alongside established lithium-ion technologies.

Flow Batteries: Principles & Redox Chemistries

ARCHITECTURE Basic Principle



Electrolyte tanks, pumps, cell stack & ion exchange membrane store energy externally in liquid electrolytes.

CHEMISTRIES Redox Systems



Vanadium redox (VRFB) leads commercial use alongside emerging iron-chromium and organic liquid chemistries.

SCALABILITY Decoupled Power



Independent scaling of power (stack size) and energy (tank volume), ideal for long-duration storage needs.

LONGEVITY Cycle Life



Exceptional operational life (20,000+ cycles) with near-zero active material degradation over decades.

INFRASTRUCTURE Balance of Plant



Larger physical footprint and active pumping balance-of-plant requirements suited for stationary installations.



TECHNOLOGY POSITIONING

Redox Flow: The Standard for Multi-Hour Grid Storage

Redox flow batteries represent the primary category within flow battery technology. By decoupling energy capacity from power rating, they excel in long-duration grid-scale applications where spatial footprint is secondary to life-cycle economics and zero-degradation thermal safety.

Solid-State: Next-Generation Architecture

ARCHITECTURE

Solid Electrolyte



Replaces liquid electrolytes with solid separators, eliminating volatile solvents and enabling lithium metal anodes.

BENEFITS

Safety & Density



Significantly reduces thermal runaway risks while boosting volumetric energy density for compact designs.

DIVERSITY

Electrolyte Types



Diverse approaches including sulfide, oxide, and polymer systems—each with unique trade-offs.

BOTTLENECKS

Interface & Mfg



High interfacial resistance, dendrite formation, and high-cost precision manufacturing hinder scale-up.

COMMERCIAL Deployment Status



Limited to niche applications today; mass EV adoption expected late 2020s or early 2030s.



TECHNOLOGY PERSPECTIVE

Solid-State is a Diverse Category, Not a Monolithic Solution

Solid-state technology encompasses distinct chemical routes—sulfides offer high conductivity but moisture sensitivity, oxides provide safety but high rigidity, and polymers allow easier processing with lower room-temperature performance. Commercial maturity varies, making targeted deployment essential.

Zinc-Based Systems: Sustainable & Safe Storage

CHEMISTRIES Zinc-Ion Tech



Rechargeable intercalation systems using mild aqueous electrolytes for non-flammable operation.

ARCHITECTURE Zinc-Bromine



Hybrid flow system separating energy and power, utilizing liquid electrolyte plating mechanics.

SUPPLY CHAIN Abundant Zinc



Leverages low-cost, globally available materials, bypassing critical supply bottlenecks of lithium and cobalt.

PERFORMANCE Energy Density



Moderate energy density compared to lithium, prioritizing intrinsic safety and long-duration storage economics.

ECOSYSTEM Maturity Level



Zinc-bromine sees commercial stationary use; zinc-ion advances rapidly toward commercial scale.



SYSTEM ARCHITECTURE DISTINCTION

Zinc-ion and Zinc-bromine flow represent distinct technical approaches.

While zinc-ion relies on solid-state or aqueous intercalation chemistry inside closed cells, zinc-bromine operates as a redox flow system with external tanks and pumps. Both leverage abundant zinc for enhanced safety and sustainability, serving complementary roles in non-lithium energy storage.

Metal-Air & Next-Gen Chemistries

HIGH ENERGY DENSITY Zinc-Air



Uses atmospheric oxygen to boost capacity. Offers low cost & safety, but faces severe rechargeability & air-electrode limits.

MULTI-DAY STORAGE Iron-Air



Solves ultra-low-cost 100hr grid storage via reversible rusting. Accepts low round-trip efficiency & heavy system footprint.

ULTIMATE HORIZON Lithium-Air



Promises gasoline-like theoretical energy density. Early research stage blocked by material stability & side reactions.

SYSTEM METRICS Key Trade-offs



Trades power density & round-trip efficiency for massive volumetric/gravimetric potential & ultra-low capex.

ECOSYSTEM Maturity Level



Iron-air enters pilot grid deployments; zinc-air targets niche uses; lithium-air remains long-term R&D.



TECHNOLOGY POSITIONING & BOTTLENECKS

Metal-Air Prioritizes Extreme Duration and Economics Over Efficiency

Metal-air chemistries unlock open-system energy scaling by drawing oxygen from ambient air. While offering unprecedented theoretical capacities for multi-day storage, commercial adoption hinges on overcoming major technical hurdles: low round-trip efficiency (<60%), limited power density, air-electrode degradation, and complex balance-of-plant management.

The Technology-Selection Framework

INPUT STEP 01

Operating Profile



Defines load patterns, duty cycles, charge rates, and environmental conditions required by the target application.

INPUT STEP 02

Characteristics



Establishes essential attributes including energy density, power response, safety margins, and footprint constraints.

CORE EVALUATION

Tech Selection



Matches application requirements against candidate chemistries based on performance, maturity, and risk profiles.

IMPLEMENTATION

System Design



Integrates chosen cells with optimal thermal management, balance-of-plant, and battery management systems (BMS).

STRATEGIC GOAL

Lifecycle Value



Maximizes long-term economic returns, operational reliability, and levelized cost of storage (LCOS) over system life.



FRAMEWORK METHODOLOGY

Holistic Evaluation Balances Technical Performance and Lifecycle Economics

Selecting the optimal storage technology requires aligning application operating profiles and mandatory characteristics with appropriate cell chemistries. System design decisions directly impact long-duration reliability, safety, and ultimate levelized cost of energy storage.

Technology Comparison: One Common Framework

Technology	Main Strength	Main Trade-off	Maturity
LFP	Safety, cycle life, mature deployment	Energy density	Commercial
NMC	Energy density	Material, thermal and cost considerations	Commercial
Sodium-ion	Material diversification, potential cost	Lower energy density, developing ecosystem	Commercializing
Redox flow	Long-duration potential, decoupled P/E	Footprint, balance of plant	Commercial*
Solid-state	Potential safety and energy density	Manufacturing and interface challenges	Emerging
Zinc-based	Material availability, diverse architectures	Energy density and maturity vary	Emerging*
Metal-air	Long-duration potential	Rechargeability, efficiency, power density	Emerging



KEY TAKEAWAY: No single chemistry solves all use cases. Commercial chemistries (LFP, NMC) dominate current deployment, while emerging options target niche application trade-offs like ultra-long duration or material availability.

Application Determines Technology Selection

Application	Important Characteristics
Frequency regulation	Fast response, power capability
Solar shifting	Energy capacity, duration, cycle life
Peak shaving	Power, tariff profile, dispatch control
Long-duration storage	Energy cost, duration, lifecycle
Backup power	Reliability, availability, safety
Fast charging support	High power, response, grid constraints

STRATEGIC SELECTION METHODOLOGY

Application Requirements Drive Battery Selection

Key Message: Application → operating profile → required battery characteristics → technology selection.

What Makes Charging Fast?

CORE CHARGING SPEED FACTORS

Charging Power & Acceptance

350 kW is a peak rating, not a continuous guarantee. Vehicle must accept power.

Charging Curve & State of Charge

Speeds taper as SoC rises to protect battery health and prevent plating.

Temperature, Chemistry & Thermal Mgmt

Cell chemistry limits and thermal dissipation dictate safe energy intake.

TECHNOLOGY DEVELOPMENTS

High-Power DC & 800V+ Architectures

Higher voltage reduces current, heat generation, and cable thickness.

Improved Chemistries & Preconditioning

Advanced materials & thermal pre-heating optimize cell acceptance.

Smart Control & Thermal Systems


Active liquid cooling and dynamic vehicle-to-charger protocols.



REAL-WORLD APPLICATION & KEY TAKEAWAY

Peak Charger Power ≠ Guaranteed Charging Speed

A 350 kW charger is only a maximum delivery rating. Actual charging speed is governed by the vehicle's battery acceptance rate, current State of Charge (SoC), active thermal management, and cell chemistry restrictions. Modern advancements—such as 800V architectures, active liquid cooling, intelligent control protocols, and automated battery preconditioning—work together to sustain higher charging power for longer periods across the session.



Safety is a System Property

DEFENSE-IN-DEPTH LAYERS

1. Cell & Module Design — Robust chemistry, physical isolation, mechanical damage protection

2. BMS & Thermal Management — Overcharge/discharge prevention, active cooling

3. Detection & Suppression — Gas/fire detection, active fire suppression systems

4. Isolation & Emergency Response — Propagation barriers, system shutdown, safety standards

RISKS & MITIGATION

Thermal Runaway & Propagation — Cell/module barriers

Electrical Overcharge / Short Circuit — BMS protection

Mechanical Damage & Gas Risk — Gas/fire detection

Standards & Testing Compliance — Rigorous validation



KEY TAKEAWAY

Safety is a Cell-to-System Engineering Issue

Safety cannot be achieved through battery chemistry alone. It requires an integrated, multi-layered defense architecture across cell design, module structures, BMS monitoring, active thermal management, early gas/fire detection, suppression, isolation protocols, and compliance with stringent testing standards to ensure true operational safety.





Cell Technology Determines BESS Performance

FOUNDATION Chemistry



Creates the core possibilities: energy density, voltage, power capability, safety, and material availability.

QUALITY Cell Design



Cell design and manufacturing determine consistency: capacity, resistance, matching, and reliability.

DEGRADATION Operations



Operating conditions determine ageing: temperature, C-rate, depth of discharge, SOC, and charging strategy.

INTEGRATION System Eng.



Converts cell capability into performance via BMS, thermal management, PCS, EMS, and protection.

EVALUATION Full Lifecycle



Considers total value: performance, degradation, safety, total cost, maintainability, and recycling.



STRATEGIC TAKEAWAY

Right Chemistry and Engineering Drive Optimal Application Fit

The future of BESS is not defined by one “best” battery chemistry—it is defined by selecting the right cell technology for the required application and operating profile. Aligning chemistry, manufacturing, operational strategy, and system engineering ensures optimal performance and lifetime value.